

SONDE IN FIBRA DI VETRO

La serie in fibra di vetro con rivestimento in polipropilene, disponibile in differenti diametri da 3 mm a 11 mm, è adatta per applicazioni rettilinee.



aspo raccoglitore verticale
vertical winder reel



aspo raccoglitore orizzontale
horizontal winder reel



aspo raccoglitore verticale carrellato
vertical winder reel with carriage

FIBREGLASS DUCT RODS

The fiberglass series with polypropylene lining is available in different diameters from 3 mm to 11 mm. Fibreglass duct rods have the highest insertion force and are suitable for straight applications.

Codice Code	Descrizione Description	Tipologia terminali Terminal type	Diametro \varnothing Diameter \varnothing (mm)	Colore Colour	Lunghezza Length (m)	Conf. (pz) PHS (pcs)
SND-FV4520ASPV	sonda passacavi in fibra di vetro \varnothing 4,5 mm con rivestimento esterno in polipropilene completa di raccordi iniziale/finale M5 (SND-621.ACC) e ogiva iniziale con foro(SND-911.ACC), montata su aspo raccoglitore verticale in acciaio zincato \varnothing 330 mm. <i>\varnothing 4.5 mm fibreglass duct rod with external lining in polypropylene with M5 (SND-621.ACC) starting/ending connector and starting holed spinner (SND-911.ACC), mounted on vertical winder reel in zinc-plated steel \varnothing 330 mm</i>	filettato threaded	4,5	arancio RAL2004 orange RAL2004	20	1
SND-FV4530ASPV					30	1
SND-FV4540ASPV					40	1
SND-FV4550ASPV					50	1
SND-FV4560ASPV					60	1
SND-FV4570ASPV					70	1
SND-FV4580ASPV					80	1
SND-FV6040ASPO					sonda passacavi in fibra di vetro \varnothing 6 mm con rivestimento esterno in polipropilene completa di raccordi iniziale/finale M6 (SND-622.ACC) e ogiva iniziale con foro (SND-912.ACC), montata su aspo raccoglitore orizzontale in acciaio zincato \varnothing 550 mm. <i>\varnothing 6 mm fibreglass duct rod with external lining in polypropylene with M6 (SND-622.ACC) starting/ending connector and starting holed spinner (SND-912.ACC), mounted on horizontal winder reel in zinc-plated steel \varnothing 550 mm</i>	filettato threaded
SND-FV6050ASPO	50	1				
SND-FV6060ASPO	60	1				
SND-FV6080ASPO	80	1				
SND-FV6100ASPO	100	1				
SND-FV9060ASPV	sonda passacavi in fibra di vetro \varnothing 9 mm con rivestimento esterno in polipropilene completa di raccordi iniziale/finale M12 (SND-623.ACC) e ogiva iniziale con grillo (SND-932.ACC), montata su aspo raccoglitore verticale carrellato in acciaio zincato \varnothing 790 mm. <i>\varnothing 9 mm fibreglass duct rod with external lining in polypropylene with M12 (SND-623.ACC) starting/ending connector and starting holed spinner (SND-915.ACC), mounted on winder reel, vertical carriage, zinc-plated steel \varnothing 790 mm.</i>	filettato threaded	9	arancio RAL2004 orange RAL2004	60	1
SND-FV9080ASPV					80	1
SND-FV9100ASPV					100	1
SND-FV110250CR	sonda passacavi in fibra di vetro \varnothing 11 mm con rivestimento esterno in polipropilene completa di raccordi iniziale/finale M12 (SND-624.ACC) e ogiva iniziale con grillo (SND-932.ACC), montata su aspo raccoglitore verticale carrellato in acciaio zincato \varnothing 1000 mm largo 230 mm. <i>\varnothing 11 mm fibreglass duct rod with external lining in polypropylene with M12 (SND-624.ACC) starting/ending connector and starting holed spinner (SND-915.ACC), mounted on vertical winder reel, with carriage, in zinc-plated steel \varnothing 1000 mm, width 230 mm</i>	filettato threaded	11	arancio RAL2004 orange RAL2004	250	1
SND-FV110300CR					300	1